

- <rubout> Erases the last character typed, echoing erased characters within slashes.
- <control-B> Exits from XYBASIC and returns the user to the resident operating system.
- <control-C> Interrupts program execution, prints break message and returns to direct mode.
- <control-G> May be used only within quoted strings in PRINT commands; "prints" as an audible bell or beep on most console devices.
- <control-H> Erases the last character typed and echoes <control-H> to backspace the cursor on a CRT.
- <control-O> Suppresses console output until next <control-O> or until an error, an INPUT command or a return to direct mode occurs.
- <control-P> Echoes all output to the selected LST device until next <control-P> typed.
- <control-Q> Resumes execution suspended by <control-S>.
- <control-R> Retypes the current input line.
- <control-S> Suspends program execution until <control-S> or <control-Q> typed.
- <control-U> Deletes the current input line.

The following characters may be used during line editing in editing versions of XYBASIC.

- <return> Terminates editing and returns to direct mode.
- <printable> Printable characters are inserted in the line at current cursor position.
- <rubout> Delete character left of cursor.
- <control-B> [Boot] Exits from XYBASIC and returns to operating system or monitor.
- <control-C> Terminates editing and returns to direct mode, leaving previous contents of line being edited unchanged.
- <control-D> [Delete] Deletes character right of the cursor.
- <control-E> [Edit] Enters the editor with contents of most recently typed line.
- <control-F> [Find] Moves cursor to right of next occurrence of <printable character> typed after <control-F>; echoes <control-G> and leaves cursor unchanged if not found.
- <control-G> [Bell] Inserts <control-G> (bell or beep) in line.